

## GR Product Notes



### CARD-PUNCH COUPLER

The new 1791 Card-Punch Coupler converts the binary-coded digital output of the GR 1680-A Automatic Capacitance Bridge into the 10-line decimal-coded contact closures required by an IBM 526 Printing Summary Punch. Up to 22 digits of paral-

lel data can be accepted from one or more sources. Since the coupler is a systems component, in some instances requiring custom treatment of connections, price will be quoted on an individual basis.

### GR900 ADAPTOR AND AIR-LINE SETS

Now available are complete sets of GR900 precision adaptors and reference air lines, mounted in mahogany cases with foamed-plastic inserts. The 0900-9451 GR900 Precision-Adaptor Set includes all the adaptors needed to mate GR900 connectors with male and female BNC, C, N, SC, OSM\*/BRM, TNC, Amphenol APC-7, Precifix 7 mm, and GR874 connectors.

The 0900-9452 GR900 Reference Air-Line Set contains one each of the

six lengths (5, 6, 7.5, 10, 15, and 30 cm) of TYPE 900-LZ Reference Air Lines, plus a 900-WN4 Short-Circuit Termination and a 900-WO4 Open-Circuit Termination, both of which are commonly used with the air lines.

The storage case alone is also available, for those who would like to give their GR900 components the maximum protection against damage and dirt.

\*OSM is a registered trademark of Omni-Spectra, Inc.



### AMPLITUDE-REGULATING POWER SUPPLY

The TYPE 1263 Amplitude-Regulating Power Supply is now the 1263-C, the new suffix denoting a regulated dc heater supply for improved oscillator performance and a relocated output-rectifier connector for more convenient installation in relay racks.